

Review of "Achieving Secure, Scalable, and Fine-grained Data Access Control in Cloud Computing"

U.Jyothi K., Nagi Reddy, B. Ravi Prasad

M.tech (CSE) Student in CSE PRRCET Medak (Dist), Andhra Pradesh India 502 300

jyothi1253@gmail.com

Asst Professor in CSE PRRCET Medak (Dist), Andhra Pradesh India 502 300

nrkandukuri@yahoo.co.in

Asst Professor in CSE PRRCET Medak (Dist), Andhra Pradesh India 502 300

rprasad.boddu@gmail.com

ABSTRACT

Cloud computing is an emerging computing paradigm in which resources of the computing infrastructure are provided as services over the Internet. As promising as it is, this paradigm also brings forth many new challenges for data security and access control when users outsource sensitive data for sharing on cloud servers, which are not within the same trusted domain as data owners. To keep sensitive user data confidential against untrusted servers, existing solutions usually apply cryptographic methods by disclosing data decryption keys only to authorized users. However, in doing so, these solutions inevitably introduce a heavy computation overhead on the data owner for key distribution and data management when fine-grained data access control is desired, and thus do not scale well. The problem of simultaneously achieving fine-grainedness, scalability, and data confidentiality of access control actually still remains unresolved.

This paper addresses this challenging open issue by, on one hand, defining and enforcing access policies based on data attributes, and, on the other hand, allowing the data owner to delegate most of the computation tasks involved in fine-grained data access control to untrusted cloud servers without disclosing the underlying data contents. We achieve this goal by exploiting and uniquely combining techniques of attribute-based encryption (ABE), proxy re-encryption, and lazy re-encryption. Our proposed scheme also has salient properties of user access privilege confidentiality and user secret key accountability. Extensive analysis shows that our proposed scheme is highly efficient and provably secure under existing security models.

Keywords: Cloud Computing, Data Security, ABE (attribute based encryption)

1 Introduction

Cloud computing is a promising computing paradigm which recently has drawn extensive attention from both academia and industry. By combining a set of existing and new techniques from research areas such as Service-Oriented Architectures (SOA) and virtualization, cloud computing is regarded as such a computing paradigm in which resources in the computing infrastructure are provided as services over the Internet. Along with this new paradigm, various business models are developed, which can be described by terminology of "X as a service (XaaS)" where X could be software, hardware, data storage, and etc. Successful examples

are Amazon's EC2 and S3, Google App Engine and Microsoft Azure which provide users with scalable resources in the pay-as-you-use fashion at relatively low prices. For example, Amazon's S3 data storage service just charges \$0.12 to \$0.15 per gigabyte-month. As compared to building their own infrastructures, users are able to save their investments significantly by migrating businesses into the cloud. With the increasing development of cloud computing technologies, it is not hard to imagine that in the near future more and more businesses will be moved into the cloud.

Security
As promising as it is, cloud computing is also facing many challenges that, if not well resolved, may impede its fast growth. Data security, as it exists in many other applications, is among these challenges that would raise great concerns from users when they store sensitive information on cloud servers. These concerns originate from the fact that cloud servers are usually operated by commercial providers which are very likely to be outside of the

trusted domain of the users. Data confidential against cloud servers is hence frequently desired when users outsource data for storage in the cloud. In some practical application systems, data confidentiality is not only a security/privacy issue, but also of juristic concerns. For example, in healthcare application scenarios use and disclosure of protected health information (PHI) should meet the requirements of Health Insurance Portability and Accountability Act (HIPAA) [5], and keeping user data confidential against the storage servers is not just an option, but a requirement.

Furthermore, we observe that there are also cases in which cloud users themselves are content providers. They publish data on cloud servers for sharing and need fine-grained data access control in terms of which user (data consumer) has the access privilege to which types of data. In the healthcare case, for example, a medical center would be the data owner who stores millions of healthcare records in the cloud. It would allow data consumers such as doctors, patients, researchers and etc, to access various types of healthcare records under policies admitted by HIPAA. To enforce these access policies, the data owners on one hand would like to take advantage of the abundant resources that the cloud provides for efficiency and economy; on the other hand, they may want to keep the data contents confidential against cloud servers.

As a significant research area for system protection, data access control has been evolving in the past thirty years and various techniques have been developed to effectively implement fine-grained access control, which allows flexibility in specifying differential access rights of individual users. Traditional access control architectures usually assume the data owner and the servers storing the data are in the same trusted domain, where the servers are fully entrusted as an omniscient reference monitor responsible for defining and enforcing access control policies. This assumption however no longer holds in cloud computing since the data owner and cloud servers are very likely to be in two different domains. On one hand, cloud servers are not entitled to access the outsourced data content for data confidentiality; on the other hand, the data resources are not physically under the full control of authorized users. Unauthorized users, including cloud servers, are not able to decrypt since they do not have the data decryption keys. This general method actually has been widely adopted by existing works which aim at securing data storage on untrusted servers. One critical issue with this branch of approaches is how to achieve the desired security goals without introducing a high complexity on key management and data encryption. These existing works, as we will discuss in section V-C, resolve this issue either by introducing a per file access control list (ACL) for fine-grained access control, or by categorizing files into several *filegroups* for efficiency. As the system scales, however, the complexity of the ACL-based scheme the owner. For the purpose of helping the data owner enjoy fine-grained access control of data stored on untrusted cloud servers, a feasible solution would be encrypting data through certain cryptographic primitive(s), and disclosing decryption keys only would be proportional to the number of users in the system. The *filegroup*-based scheme, on the other hand, is just able to provide coarse-grained data access control. It actually still remains open to simultaneously achieve the goals of fine-grainedness, scalability, and data confidentiality for data access control in cloud computing.

In this paper, we address this open issue and propose a

secure and scalable fine-grained data access control scheme for cloud computing. Our proposed scheme is partially based on our observation that, in practical application scenarios each data file can be associated with a set of attributes which are meaningful in the context of interest. The access structure of each user can thus be defined as a unique logical expression over these attributes to reflect the scope of data files that the user is allowed to access. As the logical expression can represent any desired data file set, fine-grainedness of data access control is achieved. To enforce these access structures, we define a public key component for each attribute. Data files are encrypted using public key components corresponding to their attributes. Such a design also brings about the efficiency benefit, as compared to previous works, in that, 1) the complexity of encryption is just related the number of attributes associated to the data file, and is independent to the number of users in the system; and 2) data file creation/deletion and new user grant operations just affect current file/user without involving system-wide data file update or re-keying. One extremely challenging issue with this design is the implementation of user revocation, which would inevitably require re-encryption of data files accessible to the leaving user, and may need update of secret keys for all the remaining users. If all these tasks are performed by the data owner himself/herself, it would introduce a heavy computation overhead on him/her and may also require the data owner to be always online. To resolve this challenging issue, our proposed scheme enables the data owner to delegate tasks of data file re-encryption and user secret key update to cloud servers without disclosing data contents or user access privilege information. We achieve our design goals by exploiting a novel cryptographic primitive, namely key policy attribute-based encryption (KP-ABE), and uniquely combine it with the technique of proxy re-encryption (PRE) and lazy re-encryption.

Main contributions of this paper can be summarized as follows. 1) To the best of our knowledge, this paper is the first that simultaneously achieves fine-grainedness, scalability and data confidentiality for data access control in cloud computing;

2) Our proposed scheme enables the data owner to delegate most of computation intensive tasks to cloud servers without disclosing data contents or user access privilege information;

3) The proposed scheme is provably secure under the standard security model. In addition, our proposed scheme is able to support user accountability with minor extension.

The rest of this paper is organized as follows. Section II discusses cloud computing review. Section III reviews some technique preliminaries pertaining to our construction. Section IV presents our construction. In section V, we analyze our proposed scheme in terms of its security and performance. We conclude this paper in Section VI.

2 Cloud computing Review

A study conducted by Version One found that 41% of senior IT professionals actually don't know what cloud computing is and two-thirds of senior finance professionals are confused by the concept, highlighting the young nature of the technology.

An Aberdeen Group study found that disciplined companies achieved on average an 18% reduction in their IT budget from cloud computing and a 16% reduction in data center power costs.

Cloud computing is a general term for anything that involves delivering hosted services over the Internet. These services are broadly divided into three categories: Infrastructure-as-a-Service (IaaS), Platform-as-a-Service (PaaS) and Software-as-a-Service (SaaS). The name cloud computing was inspired by the cloud symbol that's often used to represent the Internet in flow charts and diagrams.

Cloud computing is the delivery of computing as a service rather than a product, whereby shared resources, software, and information are provided to computers and other devices as a metered service over a network (typically the Internet).

Layers

Once an internet protocol connection is established among several computers, it is possible to share services within any one of the following layers represented in fig1.

a) Client

Users access cloud computing using networked client devices, such as desktop computers, laptops, tablets and smart phones. Some of these devices - cloud clients - rely on cloud computing for all or a majority of their applications so as to be essentially useless without it. Examples are thin clients and the browser-based Chrome book.




Figure 1: layers in cloud

b) Application

A cloud application is software provided as a service. It consists of the following: a package of interrelated tasks, the definition of these tasks, and the configuration files, which contain dynamic information about tasks at run-time.

C) Platform

Cloud platform services, also known as platform as a service (PaaS), deliver a computing platform and/or solution stack as a service, often consuming cloud infrastructure and sustaining cloud applications.

d) Infrastructure

Cloud infrastructure services, also known as "infrastructure as a service" (IaaS), deliver computer infrastructure – typically a platform virtualization environment – as a service, along with raw (block) storage and networking.

e) Server

The Layers contain both hardware and software; these are the layers on the server. Products that are specifically designed for the delivery of cloud services, including multi-core processors, cloud-specific operating systems and combined offerings

Architecture

The fig.2 below represents the sample architecture of the cloud computing.




Figure 2: Cloud computing sample architecture

3.Gaining secure, scalable data cloud computing

System Models

Similar to [17], we assume that the system is composed of the following parties: the Data Owner, many Data Consumers, many Cloud Servers, and a Third Party Auditor if necessary. To access data files shared by the data owner, Data Consumers, or *users* for brevity, download data files of their interest from Cloud Servers and then decrypt. Neither the data owner nor users will be always online. They come online just on the necessity basis. For simplicity, we assume that the only access privilege for users is data file reading. Extending our proposed scheme to support data file writing is trivial by asking the data writer to sign the new data file on each update as [12] does. From now on, we will also call data files by *files* for brevity. Cloud Servers are always online and operated by the Cloud Service Provider (CSP). They are assumed to have abundant storage capacity and computation power. The Third Party Auditor is also an online party which is used for auditing every file access event. In addition, we also assume that the data owner can not only store data files but also run his own code on Cloud Servers to manage his data files. This assumption coincides with the unified ontology of cloud computing which is recently proposed by Youseff et al.

B. Security Models

In this work, we just consider Honest but Curious Cloud Servers as [14] does. That is to say, Cloud Servers will follow our proposed protocol in general, but try to find out as much secret information as possible based on their inputs. More specifically, we assume Cloud

Servers are more interested in file contents and user access privilege information than other secret information. Cloud Servers might collude with a small number of malicious users for the purpose of harvesting file contents when it is highly beneficial. Communication channel between the data owner/users and Cloud Servers are assumed to be secured under existing security protocols such as SSL. Users would try to access files either within or outside the scope of their access privileges. To achieve this goal, unauthorized users may work independently or cooperatively. In addition, each party is preloaded with a public/private key pair and the public key can be easily obtained by other parties when necessary.

C. Design Goals

Our main design goal is to help the data owner achieve fine-grained access control on files stored by Cloud Servers. Specifically, we want to enable the data owner to enforce a unique access structure on each user, which precisely designates the set of files that the user is allowed to access. We also want to prevent Cloud Servers from being able to learn both the data file contents and user access privilege information. In addition, the proposed scheme should be able to achieve security goals like user accountability and support basic operations such as user grant/revocation as a general one-to-many communication system would require. All these design goals should be achieved efficiently in the sense that the system is scalable.

TECHNIQUE PRELIMINARIES

A. Key Policy Attribute-Based Encryption (KP-ABE)

KP-ABE [15] is a public key cryptography primitive for one-to-many communications. In KP-ABE, data are associated with attributes for each of which a public key component is defined. The encryptor associates the set of attributes to the message by encrypting it with the corresponding public key components. Each user is assigned an access structure which is usually defined as an access tree over data attributes, i.e., interior nodes of the access tree are threshold gates and leaf nodes are associated with attributes. User secret key is defined to reflect the access structure so that the user is able to decrypt a ciphertext if and only if the data attributes satisfy his access structure. A KP-ABE scheme is composed of four algorithms which can be defined as follows:

Setup This algorithm takes as input a security parameter κ and the attribute universe $U = \{1, 2, \dots, N\}$ of cardinality N . It defines a bilinear group G_1 of prime order p with a generator g , a bilinear map $e : G_1 \times G_1 \rightarrow G_2$ which has the properties of *bilinearity*, *computability*, and *non-degeneracy*. It returns the public key PK as well as a system master key MK as follows

$$PK = (Y, T_1, T_2, \dots, T_N) \quad MK = (y,$$

$$t_1, t_2, \dots, t_N)$$

where $T_i \in G_1$ and $t_i \in Z_p$ are for attribute i , $1 \leq i \leq N$, and $Y \in G_2$ is another public key component. We have $T_i = g^{t_i}$ and $Y = e(g, g)^y$, $y \in Z_p$.

B. Proxy Re-Encryption (PRE)

Proxy Re-Encryption (PRE) is a cryptographic primitive in which a semi-trusted proxy is able to convert a ciphertext encrypted under Alice's public key into another ciphertext that can be opened by Bob's private key without seeing the underlying plaintext. More formally, a PRE scheme allows the proxy, given the proxy re-encryption key $rk_{a \rightarrow b}$, to translate ciphertexts under public key pk_a into ciphertexts under public key pk_b and vice versa. Please refer to [16] for more details on proxy re-encryption schemes.

OUR PROPOSED SCHEME

A. Main Idea

In order to achieve secure, scalable and fine-grained access control on outsourced data in the cloud, we utilize and uniquely combine the following three advanced cryptographic techniques: KP-ABE, PRE and lazy re-encryption. More specifically, we associate each data file with a set of attributes, and assign each user an expressive access structure which is defined over these attributes. To enforce this kind of access control, we utilize KP-ABE to escort data encryption keys

of data files. Such a construction enables us to immediately enjoy fine-grainedness of access control. However, this construction, if deployed alone, would introduce heavy computation overhead and cumbersome online burden towards the data owner, as he is in charge of all the operations of data/user management. Specifically, such an issue is mainly caused by the operation of user revocation, which inevitably requires the data owner to re-encrypt all the data files accessible to the leaving user, or even needs the data owner to stay online to update secret keys for users. To resolve this challenging issue and make the construction suitable for cloud computing, we uniquely combine PRE with KP-ABE and enable the data owner to delegate most of the computation intensive operations to Cloud Servers without disclosing the underlying file contents.

B. Definition and Notation

For each data file the owner assigns a set of meaningful attributes which are necessary for access control. Different data files can have a subset of attributes in common. Each attribute is associated with a version number for the purpose of attribute update as we will discuss later. Cloud Servers keep an attribute history list *AHL* which records the version evolution history of each attribute and PRE keys used. In addition to these meaningful attributes, we also define one dummy attribute, denoted by symbol Att_D for the purpose of key management. Att_D is required to be included in every data file's

attribute set and will never be updated. The access structure of each user is implemented by an access tree. Interior nodes of the access tree are threshold gates. Leaf nodes of the access tree are associated with data file attributes. For the purpose of key management, we require the root node to be an AND gate (i.e., n -of- n threshold gate) with one child being the leaf node which is associated with the dummy attribute, and the other child node being any threshold gate. The dummy attribute will not be attached to any other node in the access tree. Fig.1 illustrates our definitions by an example. In addition, Cloud Servers also keep a user list UL which records ID s of all the valid users in the system. Fig.2 gives the description of notation to be used in our scheme

Notation	Description
PK, MK	system public key and master key
τ_i	public key component for attribute i
t_i	master key component for attribute i
SK	user secret key
sk_i	user secret key component for attribute i
E_i	ciphertext component for attribute i
I	attribute set assigned to a data file
DEK	symmetric data encryption key of a data file
P	user access structure
LP	set of attributes attached to leaf nodes of P
Att_D	the dummy attribute
UL	the system user list
AHL_i	attribute history list for attribute i
$rk_{i \rightarrow \bar{i}}$	proxy re-encryption key for attribute i from its current version to the updated version \bar{i}
$\delta_{O,X}$	the data owner's signature on message X

Fig. 2: Notation used in our scheme description

C. Scheme Description

For clarity we will present our proposed scheme in two levels: *System Level* and *Algorithm Level*. At system level, we describe the implementation of high level operations, i.e.,

System Setup, *New File Creation*, *New User Grant*, and *User Revocation*, *File Access*, *File Deletion*, and the interaction between involved parties. At algorithm level, we focus on the implementation of low level algorithms that are invoked by system level operations.

1) *System Level Operations*: System level operations in our proposed scheme are designed as follows.

System Setup In this operation, the data owner chooses a security parameter κ and calls the algorithm level interface $ASetup(\kappa)$, which outputs the system public parameter PK and the system master key M

κ . The data owner then signs each component of PK and sends PK along with these signatures to Cloud Servers.

New File Creation Before uploading a file to Cloud Servers, the data owner processes the data file as follows.

- select a unique ID for this data file;
- randomly select a symmetric data encryption key R
 $DEK \leftarrow \mathcal{K}$, where \mathcal{K} is the key space, and encrypt the data file using DEK ;
- define a set of attribute I for the data file and encrypt DEK with I using KP-ABE, i.e., $(E, \{E_i\}_{i \in I}) \leftarrow AEncrypt(I, DEK, PK)$.




Fig. 3: Format of a data file stored on the cloud

Finally, each data file is stored on the cloud in the format as is shown in Fig.3.

Summary

In our proposed scheme, we exploit the technique of hybrid encryption to protect data files, i.e., we encrypt data files using symmetric DEK s and encrypt DEK s with KP-ABE. Using KP-ABE, we are able to immediately enjoy fine-grained data access control and efficient operations such as file creation/deletion and new user grant. To resolve the challenging issue of user revocation, we combine the technique of proxy re-encryption with KP-ABE and delegate most of the burdensome computational task to Cloud Servers. We achieve this by letting Cloud Servers keep a partial copy of each user's secret key, i.e., secret key components of all but one (dummy) attributes. When the data owner redefines a certain set of attributes for the purpose of user revocation, he also generates corresponding proxy re-encryption keys and sends them to Cloud Servers. Cloud Servers, given these proxy re-encryption keys, can update user secret key components and re-encrypt data files accordingly without knowing the underlying plaintexts of data files. This enhancement releases the data owner from the possible huge computation overhead on user revocation. The data owner also does not need to always stay online since Cloud Servers will take over the burdensome task after having obtained the PRE keys. To further save computation overhead of Cloud Servers on user revocation, we use the technique of lazy re-encryption and enable Cloud Servers to "aggregate" multiple successive secret key update/file re-encryption operations into one, and thus statistically save the computation overhead.

A. Security Analysis

We first analyze security properties of our proposed scheme, starting with the following immediately available properties.

1) *Fine-grainedness of Access Control*: In our proposed scheme, the data owner is able to define and enforce expressive and flexible access structure for each user. Specifically, the access structure of each user is defined as a logic formula over data file attributes, and is able to represent any desired data file set.

2) *User Access Privilege Confidentiality*: Our proposed scheme just discloses the leaf node information of a user access tree to Cloud Servers. As interior nodes of an access tree can be any threshold gates and are unknown to Cloud Servers, it is hard for Cloud Servers to recover the access structure and thus derive user access privilege information.

3) *User Secret Key Accountability*: This property can be immediately achieved by using the enhanced construction of KP-ABE [19] which can be used to disclose the identities of key abusers.

Now we analyze data confidentiality of our proposed scheme by giving a cryptographic security proof.

Data Confidentiality: We analyze data confidentiality of our proposed scheme by comparing it with an intuitive scheme in which data files are encrypted using symmetric *DEKs*, and *DEKs* are directly encrypted using standard KP-ABE. In this intuitive scheme just ciphertexts of data files are given to Cloud Servers.

. Performance Analysis

This section numerically evaluates the performance of our proposed scheme in terms of the computation overhead introduced by each operation as well as the ciphertext size.

1) *Computation Complexity*: We analyze the computation complexity for the following six operations: *system setup*, *new file creation*, *file deletion*, *new user grant*, *user revocation*, and *file access*.

System Setup In this operation, the data owner needs to define underlying bilinear groups, and generate P K and M K . As is described in Section III-A, the main computation overhead for the generation of P K and M K is introduced by the N group multiplication operations on G_1 .

New File Creation The main computation overhead of this operation is the encryption of the data file using the symmetric *DEK* as well as the encryption of the *DEK* using KP-ABE. The complexity of the former depends on the size of the underlying data file and inevitable for any cryptographic method. The computation overhead for the latter consists of $|I|$ multiplication operations on G_1 and 1 multiplication operation on G_2 , where I denotes the attribute set

File Deletion This operation just involves the data owner and Cloud Servers. The former needs to compute one signature and the latter verifies this signature.

New User Grant This operation is executed interactively by the data owner, Cloud Servers, and the user. The computation overhead for the data owner is mainly composed of the generation of the user secret key and encryption of the user secret key using the user's public key. The former accounts for $|L|$ multiplication operations on G_1 , where L denotes the set of leaf nodes of the access tree. The latter accounts for one PKC operation, e.g., RSA encryption. The main overhead for Cloud Servers is one signature verification. The user needs to do two PKC operations, one for data decryption and the other for signature verification.

User Revocation This operation is composed of two stages. The second stage can actually be amortized as the file access operation. Here we just counts the operation overhead for the first stage. That for the second stage will be included in the file access operation. The first stage occurs between the data owner and Cloud Servers. The computation overhead for the data owner is caused by the execution of *AM inimalSet* and *AU pdateAtt* as well as the generation of his signatures for the public key components. The complexity of algorithm *AM inimalSet* is actually mainly contributed by the CNF conversion operation which can be efficiently realized by existing algorithms such as [20] (with the complexity linear to the size of the access structure). Assuming the size of the minimal set returned by *AM inimalSet* is D , $D \leq N$, the computation overhead for *AU pdateAtt* is mainly contributed by D multiplication operations on G_1 . In addition, the data owner also needs to compute D signatures on public key components. The computation overhead on Cloud Servers in this stage is negligible. When counting the complexity of user revocation, we use N instead of the size of the access structure since in practical scenarios *AM inimalSet* is very efficient if we limit the size of access structure (without affecting system scalability), but each signature or multiplication operation on G_1 is expensive.

File Access This operation occurs between Cloud Servers and the user. For Cloud Servers, the main computation overhead is caused by the execution of algorithm *AU pdateSK* and algorithm *AU pdateAtt4F ile*. In the worst case, the algorithm *AU pdateSK* would be called $|L| - 1$ times, which represents $|L|-1$ multiplication operations on G_1 . Each execution of the algorithm *AU pdateAtt4F ile* accounts for one multiplication operation on G_1 . In the worst case, Cloud Servers need to call *AU pdateAtt4F ile* N times per file access. Our lazy re-encryption solution will greatly reduce the average system-wide call times of these two algorithms from statistical point of view. File decryption needs $|L|$ bilinear pairing in the worst case. Fig.7 summarizes the computation complexity of our proposed scheme.

Operation	Complexity
File Creation	$O(I)$
File Deletion	$O(1)$
User Grant	$O(L)$
User Revocation	$O(N)$

Fig. 7: Complexity of our proposed scheme

2) *Ciphertext Size*: As is depicted in Section IV-C, the ciphertext is composed of an ID, a header, and a body. The body is just the data block. The header for each data file is composed of an attribute set I , one group element on G_2 , and $|I|$ group elements on G_1 .

C. Related Work

Existing work close to ours can be found in the areas of “shared cryptographic file systems” and “access control of outsourced data”.

In [11], Kallahalla et al proposed Plutus as a cryptographic file system to secure file storage on untrusted servers. Plutus groups a set of files with similar sharing attributes as a file-group and associates each file-group with a symmetric lockbox-key. Each file is encrypted using a unique file-block key which is further encrypted with the

lockbox-key of the file-group to which the file belongs. If the owner wants to share a file-group, he just delivers the corresponding lockbox-key to users. As the complexity of key management is proportional to the total number of file-groups, Plutus is not suitable for the case of fine-grained access control in which the number of possible “file-groups” could be huge.

In [12], Goh et al proposed SiRiUS which is layered over existing file systems such as NFS but provides end-to-end security. For the purpose of access control, SiRiUS attaches each file with a meta data file that contains the file’s access control list (ACL), each entry of which is the encryption of the file’s file encryption key (FEK) using the public key of an authorized user. The extension version of SiRiUS uses NNL broadcast encryption algorithm [21] to encrypt the FEK of each file instead of encrypting it with each individual user’s public key. As the complexity of the user revocation solution in NNL is proportional to the number of revoked users, SiRiUS has the same complexity in terms of each meta data file’s size and the encryption overhead, and thus is not scalable.

Ateniese et al [13] proposed a secure distributed storage scheme based on proxy re-encryption. Specifically, the data owner encrypts blocks of content with symmetric content keys. The content keys are all encrypted with a master public key, which can only be decrypted by the master private key kept by the data owner. The data owner uses his master private key and user’s public key to generate proxy re-encryption keys, with which the semi-trusted server can then convert the ciphertext into that for a specific granted user and fulfill the task of access control enforcement. The main issue with this scheme is that collusion between a malicious server and any single malicious user would expose decryption keys of all the encrypted data and compromise data security of the system completely. In addition, user access privilege is not protected from the proxy server. User secret key accountability is neither supported.

In [14], Vimercati et al proposed a solution for securing data storage on untrusted servers based on key derivation methods [22]. In this proposed scheme, each file is encrypted with a symmetric key and each user is assigned a secret key. To grant the access privilege for a user, the owner creates corresponding public tokens from which, together with his secret key, the user is able to derive decryption keys of desired files. The owner then transmits these public tokens to the semi-trusted server and delegates the task of token distribution to it. Just given these public tokens, the server is not able to derive the decryption key of any file. This solution introduces a minimal number of secret key per user and a minimal number of encryption key for each file. However, the complexity of operations of file creation and user grant/revocation is linear to the number of users, which makes the scheme unscalable. User access privilege accountability is also not supported.

D. Discussion

According to the above analysis, we can see that our proposed scheme is able to realize the desired security goals, i.e., fine-grained access control, data confidentiality, user access privilege confidentiality, and user secret key accountability. The goal of scalability is also achieved since the complexity for each operation of our proposed scheme, as is shown in Fig. 7, is no longer dependent to the number of users in the system. Therefore, our proposed scheme can serve as an ideal candidate for data access control in the emerging cloud computing environment. On the contrary, existing access control schemes in related areas either lack scalability [12], [14] and fine-grainedness [11], or do not provide adequate proof of data confidentiality [13].

IV. CONCLUSION

This paper aims at fine-grained data access control in cloud computing. One challenge in this context is to achieve fine-grainedness, data confidentiality, and scalability simultaneously, which is not provided by current work. In this paper we propose a scheme to achieve this goal by exploiting KP-ABE and uniquely combining it with techniques of proxy re-encryption and lazy re-encryption. Moreover, our proposed scheme can enable the data owner to delegate most of computation overhead to powerful cloud servers. Confidentiality of user access privilege and user secret key accountability can be achieved. Formal security proofs show that our proposed scheme is secure under standard cryptographic models.

ACKNOWLEDGMENTS

This work was supported in part by the US National Science Foundation under grants CNS-0716306, CNS-0831628, CNS-0746977, and CNS-0831963.

REFERENCES

- [1] M. Armbrust, A. Fox, R. Griffith, A. D. Joseph, R. H. Katz, A. Konwinski, G. Lee, D. A. Patterson, A. Rabkin, I. Stoica, and M. Zaharia, "Above the clouds: A Berkeley view of cloud computing," University of California, Berkeley, Tech. Rep. USB-EECS-2009-28, Feb 2009.
- [2] Amazon Web Services (AWS), Online at <http://aws.amazon.com>.
- [3] Google App Engine, Online at <http://code.google.com/appengine/>.
- [4] Microsoft Azure, <http://www.microsoft.com/azure/>.
- [5] 104th United States Congress, "Health Insurance Portability and Accountability Act of 1996 (HIPPA)," Online at <http://aspe.hhs.gov/admsimp/pl1104191.htm>, 1996.
- [6] H. Harney, A. Colgrove, and P. D. McDaniel, "Principles of policy in secure groups," in *Proc. of NDSS'01*, 2001.
- [7] P. D. McDaniel and A. Prakash, "Methods and limitations of security policy reconciliation," in *Proc. of SP'02*, 2002.
- [8] T. Yu and M. Winslett, "A unified scheme for resource protection in automated trust negotiation," in *Proc. of SP'03*, 2003.
- [9] J. Li, N. Li, and W. H. Winsborough, "Automated trust negotiation using cryptographic credentials," in *Proc. of CCS'05*, 2005.
- [10] J. Anderson, "Computer Security Technology Planning Study," Air Force Electronic Systems Division, Report ESD-TR-73-51, 1972, <http://seclab.cs.ucdavis.edu/projects/history/>.
- [11] M. Kallahalla, E. Riedel, R. Swaminathan, Q. Wang, and K. Fu, "Scalable secure file sharing on untrusted storage," in *Proc. of FAST'03*, 2003.
- [12] E. Goh, H. Shacham, N. Modadugu, and D. Boneh, "Sirius: Securing remote untrusted storage," in *Proc. of NDSS'03*, 2003.
- [13] G. Ateniese, K. Fu, M. Green, and S. Hohenberger, "Improved proxy re-encryption schemes with applications to secure distributed storage," in *Proc. of NDSS'05*, 2005.
- [14] S. D. C. di Vimercati, S. Foresti, S. Jajodia, S. Paraboschi, and P. Samarati, "Over-encryption: Management of access control evolution on outsourced data," in *Proc. of VLDB'07*, 2007.
- [15] V. Goyal, O. Pandey, A. Sahai, and B. Waters, "Attribute-based encryption for fine-grained access control of encrypted data," in *Proc. of CCS'06*, 2006.
- [16] M. Blaze, G. Bleumer, and M. Strauss, "Divertible protocols and atomic proxy cryptography," in *Proc. of EUROCRYPT '98*, 1998.
- [17] Q. Wang, C. Wang, J. Li, K. Ren, and W. Lou, "Enabling public verifiability and data dynamics for storage security in cloud computing," in *Proc. of ESORICS '09*, 2009.
- [18] L. Youseff, M. Butrico, and D. D. Silva, "Toward a unified ontology of cloud computing," in *Proc. of GCE'08*, 2008.
- [19] S. Yu, K. Ren, W. Lou, and J. Li, "Defending against key abuse attacks in kp-abe enabled broadcast systems," in *Proc. of SECURECOMM'09*, 2009.
- [20] D. Sheridan, "The optimality of a fast CNF conversion and its use with SAT," in *Proc. of SAT'04*, 2004.
- [21] D. Naor, M. Naor, and J. B. Lotspiech, "Revocation and tracing schemes for stateless receivers," in *Proc. of CRYPTO'01*, 2001.
- [22] M. Atallah, K. Frikken, and M. Blanton, "Dynamic and efficient key management for access hierarchies," in *Proc. of CCS'05*, 2005.